

1517L 15-inch LCD Desktop Touchmonitor

Specifications	
Model	1517L
Color	Black or White
Active Display Area	11.97 x 8.98 inches / 304 x 228 mm
Monitor Dimensions (with stand)	14.1 x 7.8 x 12.5 inches / 358 x 197 x 319 mm (dimensions vary with stand position and options selected)
Monitor Thickness	1.7 inches / 43 mm panel depth
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	15.0"
Aspect Ratio	4:3
Native (Optimal) Resolution	1024 x 768
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768 @ 60Hz, 75Hz
Colors	16.2 million
Brightness (typical)	LCD Panel: 250 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits; IntelliTouch ZB: 225 nits; IntelliTouch Pro pcap: 225 nits
Response Time – Total (typical)	16 msec
Viewing Angle (typical)	Horizontal: +/-80° or 160° total; Vertical: +/-70° or 140° total
Contrast Ratio (typical)	700:1
Video	Analog VGA on Female DE-15 connector Input Video Horizontal Sync frequency range: 31.5-60KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor input power connector - AC: IEC 60320 C6. Monitor input power signal specifications: 100-240VAC, 50/60Hz Monitor input power connector - DC: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5% Note: Optional AC-DC power adapter sold for this monitor. Adapter input connector: IEC 60320 C14 Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor): 12W; SLEEP (monitor): 1.0W; OFF (monitor): 0.8W
Weight (with stand)	Unpackaged: 4.3 kg / 9.5 lb; Packaged: 7.3 kg / 16.0 lb.
Shipping Dimensions	19.2 x 9.1 x 19.1 inches / 487 x 231 x 485 mm
Mounting Options	75 mm VESA mount, capped through-mount holes
On-Screen Display (OSD) Controls (Accessible through switches Along the bottom)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H- position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	Argentina S-mark, Australia C-Tick, Canada cUL, IC, China CCC, Europe CE, Japan VCCI, Korea KCC, e-Standby, Mexico CoC, Taiwan BSMI Mark, United States UL, FCC, International CB, RoHS, China RoHS, WEEE, IMERC
Touch Interface	Serial (RS232) and USB
Warranty	3 years standard
MTBF	50,000 hours demonstrated

Ordering Information

Model	Part Number	Technology	Interface	Bezel	Surface Treatment	Color	Availability
1517L	E523163	AccuTouch	Serial/USB	Yes	Antiglare	Black	Worldwide
	E532051	AccuTouch	Serial/USB	Yes	Antiglare	White	Worldwide
	E144246	AccuTouch	Serial/USB	No	Antiglare	Black	Worldwide
	E590483	AccuTouch	Serial/USB	No	Antiglare	White	Worldwide
	E344758	IntelliTouch	Serial/USB	Yes	Antiglare	Black	Worldwide
	E579160	IntelliTouch	Serial/USB	Yes	Antiglare	White	Worldwide
	E829550	IntelliTouch ZB	Serial/USB	No	Clear	Black	Worldwide
	E342516	IntelliTouch ZB	Serial/USB	No	Clear	White	Worldwide
	E273226	IntelliTouch ZB	Serial/USB	No	Antiglare	Black	Worldwide
	E236309	IntelliTouch ZB	Serial/USB	No	Antiglare	White	Worldwide
E648912	IntelliTouch Pro PCAP	USB	No	Antiglare	Black	Worldwide	

Optional Peripherals

Peripheral	Interface	Color	Part Number
Magnetic Stripe Reader	USB	Black	E500356
Magnetic Stripe Reader	USB	White	E233227

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. ©2015 Elo Touch Solutions, Inc. All rights reserved. 15111AES00011



- Sleek and thin design with "Built for Touch" Reliability
- 40% Energy Savings using LED Technology
- 3 Year Standard Warranty
- Integrated cable management
- Space-saving design



1717L 17-inch LED Desktop Touchmonitor

The 1717L touchmonitor is built to withstand the rigors of continuous public use with a rugged "built for touch" design. Its stylish, thin and modern look is coupled with a retail-focused feature set and is an attractive solution for commercial touchmonitor needs. It is well suited for high use public venues where point-of-sale, point-of-information, point-of-service, loyalty systems, and shelf-level and countertop interactive digital signage are found.

The 1717L is offered with a choice of touch technology. AccuTouch five-wire resistive is widely used in retail and hospitality environments based on its proven ability to survive splashing liquids, food and grease. IntelliTouch and IntelliTouch Zero-Bezel pure glass surface acoustic

wave technology delivers the ultimate in optical quality for dry retail and hospitality applications. For multi-touch applications, IntelliTouch Pro projected capacitive supports fast, sensitive 10-touch interaction right out of the box.

The optional 3-track magnetic stripe reader (MSR) is programmable to either HID or Keyboard Emulation. It is easily installed by the user, providing an elegant, integrated solution and eliminating the need for external brackets or attachments.

The 1717L touchmonitor is environmentally friendly, lightweight and uses less power with state-of-the-art LED backlights in the display panels.



Key features:

- **Edge-to-edge Zero-bezel:**
AccuTouch resistive, IntelliTouch Zero-Bezel surface acoustic wave and IntelliTouch Pro projected capacitive multi-touch
- **Traditional Bezel:**
AccuTouch resistive and IntelliTouch surface acoustic wave
- **Antiglare or Clear glass**
- **Black or White color choices**
- **Desktop, wall or VESA mounting**
- **Internal and external power options**
- **USB and RS232 serial connections**
- **Customizable with integrated magnetic stripe reader**

Key Applications:

- Point-of-Sale
- Point-of-Information

About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including banking, gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with more than 20 million installations worldwide.

1717L 17-inch Desktop Touchmonitor

Specifications	
Model	1717L
Color	Black or white
Active Display Area	13.3 x 10.6 inches/338 x 270 mm
Monitor Dimensions (with stand)	15.4 x 8.5 x 14.2 inches / 392 x 215 x 361 mm (dimensions vary with stand position and options selected)
Monitor Thickness	1.7 inches / 43 mm panel depth
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	17.0"
Aspect Ratio	5:4
Native (Optimal) Resolution	1280 x 1024
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768, @60Hz, 75Hz; 1280 x 1024 @ 60Hz, 75Hz
Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits; IntelliTouch ZB: 225 nits; IntelliTouch Pro pcap: 225 nits
Response Time – Total (typical)	7.8msec
Viewing Angle (typical)	Horizontal: +/-85° or 170° total; Vertical: +/-80° or 160° total
Contrast Ratio (typical)	1000:1
Video	Analog VGA on Female DE-15 connector; Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor input power connector - AC: IEC 60320 C6. Monitor input power signal specifications: 100-240VAC, 50/60Hz Monitor input power connector - DC: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5% Note: Optional AC-DC power adapter sold for this monitor. Adapter input connector: IEC 60320 C14 Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor): 20W; SLEEP (monitor): 1.1W; OFF (monitor): 0.8W
Weight (with stand)	Unpackaged: 5.4 kg / 11.9 lb.; Packaged: 8.3 kg/18.3 lb.
Shipping Dimensions	20.1 x 9.2 x 20 inches / 511 x 233 x 510 mm
Mounting Options	75 mm VESA mount, capped through-mount holes
On-Screen Display (OSD) Controls (Accessible through switches Along the bottom)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H- position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	Argentina S-mark, Australia C-Tick, Canada cUL, IC, China CCC, Europe CE, Japan VCCI, Korea KCC, e-Standby, Mexico CoC, Taiwan BSMI Mark, United States UL, FCC, International CB, RoHS, China RoHS, WEEE, IMERC
Touch Interface	Serial (RS232) and USB
Warranty	3 years standard
MTBF	50,000 hours demonstrated

Ordering Information

Model	Part Number	Technology	Interface	Bezel	Surface Treatment	Color	Availability
1717L	E877820	AccuTouch	Serial/USB	Yes	Antiglare	Black	Worldwide
	E371267	AccuTouch	Serial/USB	Yes	Antiglare	White	Worldwide
	E649473	AccuTouch	Serial/USB	No	Antiglare	Black	Worldwide
	E679434	AccuTouch	Serial/USB	No	Antiglare	White	Worldwide
	E077464	IntelliTouch	Serial/USB	Yes	Antiglare	Black	Worldwide
	E214112	IntelliTouch	Serial/USB	Yes	Antiglare	White	Worldwide
	E179069	IntelliTouch ZB	Serial/USB	No	Clear	Black	Worldwide
	E227652	IntelliTouch ZB	Serial/USB	No	Clear	White	Worldwide
	E017030	IntelliTouch ZB	Serial/USB	No	Antiglare	Black	Worldwide
	E415033	IntelliTouch ZB	Serial/USB	No	Antiglare	White	Worldwide
	E824217	IntelliTouch Pro PCAP	USB	No	Antiglare	Black	Worldwide

Optional Peripherals

Peripheral	Interface	Color	Part Number
Magnetic stripe reader	USB	Black	E500356
Magnetic stripe reader	USB	White	E233227

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8001
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. © 2015 Elo Touch Solutions, Inc. All rights reserved. 15121AEB00013

